



MEPRO MCO PRO

Closed Emitter Optic with Picatinny Mount for Rifles, Carbines, and Shotguns

This closed emitter design shields against all elements for peak performance in any environment. It features a user-selectable 3-segment SpeedRing reticle (2 MOA Dot, 2/68 SpeedRing, SpeedRing with 1.5 Mil holdover dots) with 10 Day/2 NV brightness settings.

0.5 MOA windage and elevation adjustments per click at 100 yards. Setting 5 provides an impressive 25,000+ hours of battery life, complemented by automatic and manual brightness control along with Shake Awake. The recoil block ensures alignment and zero hold. It is IP67 water/dust proof rated.

This durable optic is built for precision. A 1.93" riser is available separately for better cheek weld when wearing body armor. Step-up your defense capabilities and delve into a new level of reliability and accuracy.

PROVEN ADVANTAGES

- Closed emitter design shields against all elements
- User selectable 3-segment reticle
- 10 Day/2 NV brightness settings
- CR2032 – 25,000+ hours of battery life (setting 5)
- Automatic and Manual Brightness Control
- Shake Awake
- Recoil block for alignment and zero hold.
- IP67 Water/Dust proof rating
- 1.93" riser available separately

SPECS

- Mount: MIL-STD-1913
- Mounting Screw Torque: 35 in-lbs.
- Emitter Type: Closed
- Dimensions (LxHxW): 2.06"x 2.28" x 1.59"
- Weight (w/battery): 5.33 oz
- Body Material: 7075-T6 Aluminum
- Battery Type: CR2032
- Battery Life : 25,000 + hours (Manual setting 5)
- Sleep Mode: 1 hour, shake awake
- Auto Shut-Off: Constant On
- Reticle: 3-Segment SpeedRing (2 MOA Dot, 2/68 MOA SpeedRing, SpeedRing with 1.5 Mil holdover dots)
- Brightness Levels: 10 Daylight/2 NV
- Illumination Modes: Auto & Manual
- W/E Adjustment per click (100 yds): 0.5 MOA
- Elevation Travel: ±30 MOA
- Windage Travel: ±30 MOA
- Eye Relief: Infinite
- Parallax: (50 yds) Free

Product

MCO PRO, 3 SEGMENT, 2/68 MOA MULTI-RETICLE, RED

MCO PRO 1.93" PICATINNY RISER

P/N

901142372

901142000007

UPC

810013524550

810013525182

